

2500 Double Hung 3 1/4" Frame



Standard

3/4" Foam
 1 Sash lock
 2 Sash locks over 40"
 Aluma tilt balances
 Anti-tilt latch mechanism
 Jamb adjusters
 Metal lock (black)
 Plastic sash stops (black)
 Plastic tilt latches (black)
 Top sash anti-drift
 White/bronze windows:
 White metal lock
 White plastic tilt latches
 Black vinyl's

Optional

Accessories
 1 1/8 x 1" L - Angle
 1 1/4 x 2" L - Angle
 1" Expander
 2" Expander
 5 1/2" Expander
 3" Dual expander
 5" Dual expander
 2 Piece caulk return
 3" Foam
 Bevel landmark frame
 Caulk return
 Caulk stop w/ return
 Child guard
 Header expander
 Internal grids
 Keyed limit lock
 Landmark frame
 Landmark grid 5/8" or 13/16"

Accessories Con't

Nailing fin
 Night vent latch
 Sash muntin
 Sheet rock receptor

Sill angle
 Stack mullion
 White sash stops
 White vinyl's
 Tie-in mullion
 Twist anchors
 90 Degree 4" corner

Hardware

Metal tilt latches

OITC/STC Rating Option

OITC: 30 w/special glazing
 STC: 35 w/special glazing

Balances

Series 97 block and tackle
 Ultra lift

Receptor/Sub Sill

Receptor 3 1/4"
 Sub sill 3 1/4"

Extended Fin Sizes

Head 1 1/4", 1 1/2", 2 1/2"
 Jamb 3/4", 1", 1 1/2", 2 1/2"
 Sill flat, 1 1/2", 2 1/2"

2 Piece Mull Covers

2"
 4"
 5 1/2"
 5 1/2" Colonial

3 Piece Mullion

1 3/4" Straight
 90 Degree
 135 Degree

Sill Covers

1 x 4 3/4"
 1 x 5"
 1 3/8 x 3 5/8"
 1 5/8 x 5"

Stool Covers

1/2 x 3"
 3/4 x 5"
 1 x 2"
 1 x 3 3/4"
 1 x 6 1/4"
 2 x 3"

Screens

Half or Full Screen

Aluminum
 Fiberglass
 Invisible
 Stainless steel
 Vandal
 Stainless steel

Common Options See Misc Page

Grid Options
 Paint Options
 Panning Options

Glass Options See Glass Page

Size

Min: 12" W x 21" Ht
 Max: Test 56" W x 91" Ht
 (Max size may vary with application)

Snap Trim & Clips

Snap Trim Size	Clip Type
3/4 x 1 1/8"	Regular
1 x 1"	Regular
1 x 1" with ext. 3"	Regular
1 x 1 1/4"	Regular
1 x 1 1/2"	Regular or Step
1 x 1 1/2" with ext. 2"	Regular or Step
1 x 1 1/2" with ext. 3/4"	Regular or Step
1 x 1 3/4"	Regular or Step
1 x 2"	Regular or Step
1 x 2 1/2"	Regular
1 x 3"	Regular
1 1/4 x 1 1/4"	Regular
1 1/2 x 1 1/4"	Regular
1 1/4 x 3 3/4"	Regular
1 1/2 x 1 1/2" with ext. 2"	Step
1 1/2 x 2 1/2" Landmark	Step
1 1/2 x 2 3/4"	Regular or Step
1 1/2 x 4 1/2"	Regular
1 3/4 x 1 1/2"	Regular
1 3/4 x 2 1/4"	Step
1 3/4 x 2 1/2"	Regular
2 1/4 x 2 1/4"	Step
2 3/4 x 2 3/4"	Step
2 7/8 x 3"	Step

Miscellaneous Options

Panning

Square

2 3/8 x 2 3/4" Preset Head
2 3/8" x 3 1/8" Preset Jamb
2 3/8" x 4 1/8" Preset Head/Sill
3/4 x 2 1/2" Head/Jamb/Sill
3/4 x 4 1/2" Head/Jamb/Sill
2 x 2" Head/Jamb/Sill
2 x 2 1/2" Head/Jamb/Sill
2 x 3" Head/Jamb/Sill
3 x 3 1/2" Head/Jamb/Sill
4 x 3 1/2" Head/Jamb/Sill

Landmark*

1 5/8 x 2 1/2" Head/Jamb/Sill
2 7/8 x 3 1/4" Head/Jamb
3 1/8 x 3 1/2" Sill
3 x 2 3/4" Head/Jamb/Sill
3 x 4" Head/Jamb/Sill
3 x 2 3/4" Head/Jamb/Sill
3 x 3" Head/Jamb/Sill
3 x 2 3/8" Head/Jamb
3 1/4 x 3 1/8" Sill
3 7/8 x 2 7/8" Head/Jamb/Sill
1/2 x 1/4" Panning Cover
2 7/8 x 4 1/2" Head/Jamb
3 7/8 x 5 5/8" Sill
3 1/2 x 4 1/2" Head/Jamb
3 7/8 x 4 3/4" Sill
4 x 4 1/4" Head/Jamb
4 1/8 x 5 1/8" Sill

*Landmark profiles vary w/sizes

*Custom profiles available

Finishes¹

Duracron
50% Kynar
70% Kynar
Anodized
Two-Tone

¹ Standard paint finishes vary according to product.

¹ Custom colors available

Grids²

Internal Grids

External Grids w/ select products

Landmark grid 5/8" or 13/16"

² Custom grid configurations are available.

OITC Ratings³

2500 Double Hung - 30 Rating
5000 Series Projected - 36 Rating
5000 Series Casement - 36 Rating
9000 Double Hung - 32 Rating
9500 Double Hung - Pending

³ All OITC rated products have special glass configurations.

Curving

Elliptical, Round Top, Trapezoid

2510 Fixed
4710 Fixed
5710 Fixed
6510 Fixed
7510 Fixed
9510 Fixed

Single-Hung w/integrated curved top

6500 Curved-Top

STC Ratings⁴

2500 Double Hung - 35 Rating
5000 Series Projected - 46 Rating
5000 Series Casement - 46 Rating
9000 Double Hung - 37 Rating
9500 Double Hung - Pending

⁴ All OITC rated products have special glass configurations.

Standard/Optional Glass

Standard w/Cardinal IG

Dual sealed insulated units

Argon gas standard with Lo E

Stainless steel spacers (except wire glass, spandrel, and various odd shapes)

Model	Standard Glass
1000	
2000	7/8" Insulated glass unit
2400	3/32" Clear in and out (cannot be tempered or used in larger applications)
2500	
2510	
3000	7/8" Insulated glass unit 1/8" Clear in and out
4000	1" Insulated glass unit 1/8" Clear in and out
5000	
6500/6800	
6510	
7500	
6200	
8000	1" Insulated glass unit 1/4" Clear in and out
9000	7/8" Insulated glass unit 1/8" Clear in and out
9500	
9510	
400/500 Door	1" Insulated glass unit 1/8" Clear tempered in and out
400/500 Transom	1 1/8" Insulated glass unit 3/16" Clear in and out

Optional Glass

3/32" Glass: Soft coat Lo E 270 (240 and 366 available)
1/8" Glass: Soft coat Lo E 270 (240 and 366 available) Frosted/Obscured Tinted colors available
3/16" Glass: Soft coat Lo E 270 (240 and 366 available) Frosted/Obscured Laminated Tinted colors available
1/4" Glass: Soft coat Lo E 270 (240 and 366 available) Frosted Clear wire Frosted wire Laminated Spandrel glass (all colors): Paint or ceramic Fritz Clear wire Tinted colors available
Optional on all windows: Insulated panels Tempered glass Louvers (available on 2510,4710,5710,6510,7510)